



P/N: 13214.01
13214.09
13214.53

Installation instructions

**2007 Jeep® Wrangler JK - Neoprene Front Seat Covers
2-door and 4-door (front seats only)**

**Parts included: (1) Front driver's side seat cover - with head rest
(1) Front passenger's side seat cover - with head rest**

NOTE: Please read instructions before installing

Instructions:

Step (1) Slide, and tilt back of seat forward

Step (2) Remove Head rest

Step (3) place upper cover over top of seat. Pull all the way down as shown.

Step (4) The neoprene cover has two holes located on top. Push fabric down and under plastic head rest lock tabs mounted into top of seat.

Step (5) Fish front flap through gap between the upper and lower seat sections. This is a tight fit. Folding seat forward may help.

Step (6) Pull rear flap tight and attach to the front flap using attached Velcro. Adjust cover for proper fit. Side ABS air bag cover should be slipped under cover as shown. Install head rest cover and attach Velcro to secure.

Step (6B)



Step(1)



Step(2)



Step (3)



Step (4)



Step (5)



Step (6A)





Step (7) Place driver's side lower cover onto seat. Fish rear buckles through gap between the upper and lower seat. This is a tight fit. Folding the seat forward may help. (see step 5)

Step (8) attach two side hooks to the underside of the seat. The hooks can be attached to any secure point under the seat.

Step (8)



Step (9)



Step (9) Slide front and rear lower straps under seat. Make sure that the front straps are inserted through the front seat adjuster arm to insure proper operation of seat slider. Connect front clip to rear clip and adjust. **DO NOT OVER TIGHTEN!!!**

Repeat for other side steps 1-9

LIMITED 90 DAY WARRANTY

that should the product or any part thereof, under normal use and conditions, be proven defective in material or workmanship within 90 DAYS from the date of original purchase, such such defect(s) will be repaired or replaced or credited at the Company's sole option.

To obtain repair or replacement within the terms of this Warranty, the product is to be delivered with proof of warranty coverage (e.g. Dated bill of sale), specification of defect(s) to the place of purchase or, with prior approval from the Company (RGA Number is required), freight pre-paid to the Company address listed below.

This warranty does not apply to any product or part thereof which, in the opinion of the Company, has suffered or been damaged through alteration, improper installation, mishandling, misuse, neglect, accident or by acts of nature. THE EXTENT OF THE COMPANY'S LIABILITY UNDER THIS WARRANTY IS LIMITED TO THE REPAIR OR REPLACEMENT PROVIDED ABOVE AND, IN NO EVENT, SHALL THE COMPANY'S LIABILITY EXCEED THE PURCHASE PRICE PAID BY PURCHASER FOR THE PRODUCT.

This Warranty is in lieu of all express warranties or liabilities. ANY IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, SHALL BE LIMITED TO THE DURATION OF THIS WRITTEN WARRANTY. ANY ACTION FOR BREACH OF ANY WARRANTY HEREUNDER INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY MUST BE BROUGHT WITHIN THE PERIOD OF 90 DAYS FROM DATE OF ORIGINAL PURCHASE.

IN NO CASE SHALL THE COMPANY BE LIABLE FOR ANY CONSEQUENTIAL OR INCIDENTAL DAMAGES FOR BREACH OF THIS OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WHATSOEVER. No person or representative is authorized to assume for the Company any liability other than expressed herein in connection with the sale of this product.

Some States do not allow limitations on how long an implied warranty lasts or the exclusion or limitation of incidental or consequential damage, so the above limitations may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

Omix-ada Inc.
460 Horizon Dr. Suite 400
Suwanee, Georgia 30024